


**100%  
RECYCLABLE**

### CTU vapour, optimised for steam ovens

Our range of Vapour Calcium Treatment Units are specially formulated for use with steam ovens and catering equipment using steam. Untreated equipment such as Combi Ovens, Pasta Cookers, Bratt Pans or Boilers will suffer from a build-up of limescale which will attack elements, oven chambers and sensors will lead to expensive breakdowns and unexpected kitchen down-time. The perfect alternative to single-use plastic water filters, the CTU can be regenerated, recycled, and returned to market making it a genuinely green filter providing not only protection for your equipment, but protecting the environment and keeping our oceans and landfill free from plastic.

Available in 10, 18, 23 and 30 litre capacities.

### Features & Benefits

- Exceptional protection for steam ovens
- Increased capacities across the range
- WRAS Approved
- Simple installation
- Protects catering equipment from limescale meaning, prolonged machine life and reduced breakdown and repair costs
- Unbeatable price per litre
- 100% Recyclable, just return to WaterCare Recycling

### CTU Vapour Specifications

Min Pressure: 1.5 bar | Max Pressure: 6 bar | Max Temperature (°C): 35  
Connections: 3/4" BSP | Operation Position: Vertical



### Protect your steam oven from the harmful effects of scale and other elements.

The Vapour Calcium Treatment Unit has been specially developed to work in harmony with your steam oven for outstanding results. Available with 3/4" inlet / outlet connections (2Port) and with additional spray arm / quench port (3 Port)

↓ **PART DESCRIPTIONS & CODES ON NEXT PAGE** ↓

## Part Descriptions & Codes

Available with 3/4" inlet / outlet connections (2-Port) and with additional spray arm / Y piece and extra hose (3-Port).

Description	Application	Dimensions H x W (mm)	Capacity (Litres)	Part No. 2P NEW	Part No. 2P REGEN	Part No. 3P NEW	Part No. 3P REGEN
CTU VAPOUR 10	6 GRID COMBI OVEN	511 x 200	7677	VAPOUR-2P-10	CTU102P-R	VAPOUR-3P-10	CTU103P-R
CTU VAPOUR 18	10 GRID COMBI OVEN	530 x 263	15355	VAPOUR-2P-18	CTU182P-R	VAPOUR-3P-18	CTU183P-R
CTU VAPOUR 23	20 GRID COMBI OVEN	670 x 263	17194	VAPOUR-2P-23	CTU232P-R	VAPOUR-3P-23	CTU233P-R
CTU VAPOUR 30	STACKED OVENS	970 x 263	29858	VAPOUR-2P-30	CTU302P-R	VAPOUR-3P-30	CTU303P-R

Oven Type/Size	Direct Fed Code (no quench)	Boiler Fed Code (with quench)
6 GRID COMBI OVEN	VAPOUR-2P-10-PK	VAPOUR-3P-10-PK
10 GRID COMBI OVEN	VAPOUR-2P-18-PK	VAPOUR-3P-18-PK
20 GRID COMBI OVEN	VAPOUR-2P-23-PK	VAPOUR-3P-23-PK
STACKED	VAPOUR-2P-23-PK	VAPOUR-3P-23-PK

Capacity based on water hardness of 12° Clarke / 180 PPM.